



# BEARING BOWER CORP.



R12LLU Bearing 2D drawings and 3D CAD models

802267 Bearings 489.026x634.873x320.675mm

Bearing No. R12LLU

Size	x41.275x11.112 mm
Outer Diameter	41,275 mm
Width	11,112 mm
D	41,275 mm
B	11,112 mm
C	11,112 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.065
EAN	4547359496031
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Inch
Long Description	3/4" Bore; 1-5/8" Outside Diameter; 7/16" Outer Race Width; 2 Seals; Ball Bearing;



## BEARING BOWER CORP.

	ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	R12LLU
Weight / LBS	0.144
Outer Race Width	0.438 Inch   11.125 Millimeter
Outside Diameter	1.625 Inch   41.275 Millimeter
Bore	0.75 Inch   19.05 Millimeter
Other Features	Deep Groove   Miniature Bearing   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Shell Alvania Prelubricated
Inner Race Width	0 Inch   0 Millimeter
bore diameter:	0.7500 in
precision rating:	Class 0
outside diameter:	1.6250 in
finish/coating:	Uncoated
overall width:	0.4375 in
bearing material:	High Carbon Chrome
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	0.4375 in
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	0.4375 in



## BEARING BOWER CORP.

snap ring included:	Without Snap Ring
maximum rpm (grease):	11000 rpm
internal clearance:	CN
fillet radius:	0.0310 in
operating temperature range:	-40 to 250 ° F
maximum rpm:	21000 RPM
dynamic load capacity:	1370 lbf
series:	R
static load capacity:	890 lbf
manufacturer product page:	<a href="#">Click here</a>